

PRODUCT SHEET & SPECIFICATIONS

i.Net

UPWARD FIRING DECORATIVE PENDANT SPEAKER

MODEL G999, G999-B

(*B - Black)



FUNCTION

The i.Net® speakers enable the masking to be distributed uniformly throughout the space. Typically hung in open ceilings, the speakers fill the space with sound that reflects off the ceiling and gently filters into the environment below to create speech privacy. i.Net speakers are perfectly matched for the OP to ensure the highest quality of sound masking, paging and audio.

Speakers used in the i.Net systems are configured with integrated RJ45 connections for plug and play and ease of installation. The speakers feature an aluminum housing, 5-inch wide dispersion and weigh approximately three pounds each. Speakers distribute sound masking, paging and/or music and are connected to a gem box.

SPEAKER ENCLOSURE

- + Aluminum Housing
- + Galvanized Perforated Grill

SPEAKER MODEL SPECIFICATIONS

- + Overall length: 24"
- + Speaker height: 6"
- + Speaker Diameter: 6"

GEM BOX SPECIFICATIONS

- + Height – 3"
- + Diameter – 4.5"

WEIGHT

- + 4lbs

LOUDSPEAKER

- + 5-inch - wide dispersion
- + Power Rating – 10 watts
- + Frequency Response – 60 – 13,000 Hz
- + Impedance – 32 Ohms
- + Resonance – 85 Hz

PAGING INPUT

- + Via OP & MPI

POWER REQUIREMENT

- + Powered by OP

WIRE REQUIREMENTS

- + All wire must be UL listed
- + Speakers use Cat 5e or equivalent, 4 twisted pair and RJ45 connectors
- + Straight cable – Pin 1 to Pin 1, Pin 2 to Pin 2, etc

INDUSTRY LISTINGS

- + ETL 62368-1