



APPLICATION NOTE

Wall and Ceiling Mounted Strobes

APPLICATION NOTE

Strobes

The Gentex strobes provide a wide range of strobe light output options in a single device. The strobes are wall and ceiling mount, low profile and offer dependable visual alarms for paging notifications. The 24VDC units are available in lens colors of amber, blue, green and red. The strobes offers tamper proof field selectable candela options.

The strobes includes a mounting bracket and also features a locking mechanism that secures the signal to the bracket without showing any screws. The strobes are ANSI/UL1638 and ANSI/UL464 listed and is also compliant with the rated candela per the polar dispersion requirements of ANSI/UL.

FEATURES AND CAPABILITIES

- Nominal voltage 24VDC
- Tamperproof field selectable candela options
- Wall Unit Dimensions: 5" (12.7 cm) H x 4.5" (11.43 cm) W x 2.5" (6.35 cm) D
- Ceiling Unit Dimensions: 6" (15.24 cm) x 2.6" (6.604 cm)
- Lens colors available: amber, blue, green and red
- Input terminals accept 12 to 18 AWG
- Faceplate available in off-white and white

ORDERING INFORMATION

Wall Mount

amber: Gentex - GESA24PWW (P/N 904-1336-002)
blue: Gentex - GESB24PWW (P/N 904-1338-002)
green: Gentex - GESG24PWW (P/N 904-1340-002)
red: Gentex - GESR24PWW (P/N 904-1342-002)

Ceiling Mount

amber: Gentex - GCSA24PCW (P/N 904-1384-002)
blue: Gentex - GCSB24PCW (P/N 904-1386-002)
green: Gentex - GCSG24PCW (P/N 904-1388-002)
red: Gentex - GCSR24PCW (P/N 904-1390-002)