

SPECTRA – i.Net®

PRODUCT SHEET & SPECIFICATIONS

DECORATIVE CEILING/WALL MOUNTED SPEAKER (MODEL G541)



FUNCTION

Lencore's wall mounted speaker is available when a surface-mounted speaker is desired or necessary due to site configuration or conditions. The speaker is capable of supporting sound masking, paging, and music.

The wall mounted speakers are typically specified in atriums, historic buildings and other specialty areas.

Speakers used in the Spectra i.Net® system are configured with integrated RJ45 connections for ease of installation.

Each speaker comes with an additional volume control with an attenuator conveniently located on the rear of the speaker for a 0 to -12 dB adjustment.

Each speaker comes with an adjustable mounting bracket that enables the speaker to be installed in various orientations.

Model

G541

DECORATIVE CEILING/ WALL MOUNTED SPEAKER

– SPEAKER ENCLOSURE

- + Speaker Body: white ABS material with bracket
- + Grill: Metal mesh grill

– SPEAKER MODEL DIMENSIONS

Height – 5"
Width – 14"
Depth - 7-1/4"

– LOUDSPEAKERS

- + Dual 3-1/2" drivers
- + wide dispersion
- + Impedance – 32 Ohms
- + Freq. Range: 160 Hz - 16 kHz

– PAGING INPUT

- + Via OP and MPI

– POWER REQUIREMENT

- + Powered by OP

– OUTPUT ADJUSTMENT

- + Volume control on rear of speaker

– WIRE REQUIREMENTS

- + Speakers use Cat 5e or equivalent, 4 twisted pair and RJ45 connectors