

## PRODUCT SHEET & SPECIFICATIONS

# i.Net STROBE ENCLOSURE

MODELS G6245 / G6246



### FUNCTION

The strobe enclosure is used to control strobes based on a pre-recorded message, page trigger, or an external trigger. When a page is made, a pre-recorded message is triggered, or a dry contact connected to the enclosure is closed, the strobe enclosure will energize the strobes to give a visual indication that a page or message is active. The strobe enclosure will ensure that all strobes are in-sync. Syncing strobes are an NFPA-72 requirement.

#### **Lencore part numbers for the enclosures:**

- G6245-1: Main enclosure, two strobe channels (6 strobes max per channel)
- G6246-1: Secondary enclosure, two strobe channels (6 strobes max per channel)
- G6245-2: Main enclosure, two independent strobe channels (6 strobes max per channel)
- G6246-2: Secondary enclosure, two independent strobe channels (6 strobes max per channel)

One main enclosure is required, and multiple secondary enclosures can be added to the main enclosure to ensure complete strobe coverage.

The strobes can be configured to all flash at the same time or like-colors only to flash at the same time.

### INPUT

+ 120VAC, 100W max. (12 strobes)

### OUTPUT

+ 24VDC for strobes

### SIZE

+ 20"W x 16"H x 6"D