

# i.Net

## AUDIO CONTROLLED RELAY SHELF

MODEL G623AUDIO



### FUNCTION

The Audio Controlled Relay shelf assembly is designed for quick convenient installation, and reliable operation in a variety of control applications. The G623AUDIO is designed to switch on line-level sources and its relatively short release delay time makes it the optimum choice for voice applications.

### FEATURES AND CAPABILITIES

- + Control Switching from Audio Signal
- + Switching from Mic or Line Signals
- + Silence sensing
- + Precise Threshold Adjustment
- + DPDT Switching Contacts

### INPUT SENSITIVITY

+ 30 dBu to 0 dBu, (adjustable, provides switching at a -20 dB threshold for signals of -10 dBu to +20 dBu)

### RELAY RELEASE DELAY

+ 0.5 to 5.0 seconds (Multi-turn adjustable)

### AUDIO INPUT

+ 10 k $\Omega$  balanced bridging

### INPUT CONNECTIONS

+ Balanced or Unbalanced

### RELAY CONTACTS

+ Double-Pole, Double-Throw

### MAXIMUM SWITCHING POWER

+ 60W (220 Vdc, 125 Vac, 2 A)

### POWER REQUIREMENT

- + 24 to 33 Vdc @ 50 mA
- + power supply included
- + 120VAC power cord included

### SHELF

- + 16-gauge steel
- + black powder coated
- + 2RU with face plate
- + 14.75" deep