

PRODUCT SHEET & SPECIFICATIONS

TANGENT® SPEAKER

(MODELS G950/G950-B/
G951-INLINE)



**Picture above shows aluminum housing*

i.Net Tangent® offers wider sound dispersion, better sound uniformity and greater sound quality.

FUNCTION

When a direct fired speaker or system is required due to site conditions or application need the i.Net Tangent® offers a commercial grade direct fired speaker using higher quality construction and sound quality than competitive systems.

Installation is simplified using plug and play Cat 5e cable with standard RJ45 connections. The i.Net Tangent® speaker is equipped with torsion springs to ensure a smooth installation in ceiling tile or gypsum board.

– WIRE REQUIREMENTS

- + All wire must be plenum rated and UL listed
- + Speakers use Cat 5e or equivalent, 4 twisted pair and RJ45 connectors, 568B wiring

– INSTALLATION

- + Assembly to fit into a round hole, cut into ceiling tile or gypsum. Two torsion springs spaced equidistant apart for secure mounting.
- + Securing the speaker to the deck or using a tile bridge is dependant on local codes and is the responsibility of the installer to determine any additional fastening that needs to take place.

– TILE BRIDGE (TB-4, sold separately)

- + The Tile Bridge is a load-bearing T-bar support designed to sustain the weight of an 7 1/8" or 4 1/2" speaker, grille and protection enclosure in suspended ceiling construction. Use of the Tile Bridge improves environmental safety and eliminates unsightly sag in 2'-by-2' and 2'-by-4' acoustic ceiling tiles.

– SPEAKER ENCLOSURE

- + G950: Aluminum Housing/White grill
- + G950-B: Aluminum Housing/Black grill
- + G951-INLINE: same as the G950 but with an internal volume adjusting screw (0 to -12 dB)
- + Grill: Metal screen, white or black with perforated 4" grill

– SPEAKER COVERAGE

- + 100 sq. ft. (nominal 10' speaker separation)

– LOUDSPEAKER

- + Power Rating – 10 watts
- + Frequency Response – 90-18 kHz
- + SPL for Masking Output: 90 dB
- + Impedance – 32 Ohms
- + Speaker Weight – 1.1 lbs
- + Overall Speaker Dimension – 5.3"
- + Depth – 5"
- + Diameter (outside plate) – 5 1/4"
- + Diameter (can) – 3 7/8"